

# PRODUCT DATASHEET

## Confidex Silverline Slim™



Versatile all-surface-RFID label with industry leading printing capabilities and excellent performance

### ELECTRICAL SPECIFICATION

#### Device type

Class 1 Generation 2 passive UHF RFID transponder

#### Air interface protocol

EPCGlobal Class1 Gen2 ISO 18000-6C

#### Operational frequency

ETSI 865 – 869 MHz

FCC 902 – 928 MHz

#### IC type

Impinj Monza 4QT™

#### Memory configuration

With Monza 4QT: EPC 128 bit; User 512 bit; TID 96 bit

#### EPC memory content

Same EPC in every label as a default

#### Read range (2W ERP)\*

On metal up to 4 m / 13 ft

On Plastic up to 3 m / 10 ft


Liquid containers up to 3 m / 10 ft

#### Applicable surface materials\*

All surfaces

#### Attachment on curved surface\*

Label can be attached on a curved surface in any orientation. For optimal performance, the following orientation is recommended.



\* Read ranges are theoretical values that are calculated for non-reflective environment. Different surface materials may have an effect on performance.

### MECHANICAL SPECIFICATION

#### Label surface

Printable white PET, Zebra 5095 resin ribbon recommended

#### Background adhesive

High performance acrylic adhesive optimized for metal and painted metal surfaces

#### Weight

1 g

#### Delivery format

1000 pcs good labels on reel, bad ones marked with "XXX" printing. Typical yield >99%

#### Pitch on reel


25,4 mm / 1"

#### Reel core inner diameter

76 mm / 3"

#### Tag dimensions

110 x 13 x 0,8 mm / 4.33 x 0.51 x 0.03"



## ENVIRONMENTAL RESISTANCE

**Operating temperature**

-35°C to +85°C / -31°F to +185°F

**Ambient temperature**

-35°C to +85°C / -31°F to +185°F

**Water resistance**

IP68, tested for 65 hours in 1m deep water

**Washing resistance**

Tolerates industrial washing with standard solvents.

Washing process should be tested in final application.

**Chemical resistance**

No physical or performance changes in:

- 168h Sulfuric acid (10%, pH 2) exposure
- 168h Motor oil exposure
- 168h Salt water (salinity 10%) exposure
- 1h NaOH (10%, pH 13) exposure


Acetone should be avoided

**Storage condition**

1 year in +20°C / 50% RH

*Environmental values are the best recommendations; resistance against different conditions depends on the combination of all influencing factors, exposure duration and chemical concentrations. Thus, product's final suitability for certain environmental conditions is recommended to be tested.*

## INSTALLATION INSTRUCTIONS



When attaching the label ensure the following

- Select a smooth surface without uneven areas below tag
- Avoid touching the background adhesive and IC location

When mounting the label with its adhesive, clean and dry the surface for obtaining the maximum bond strength. Typical cleaning solvents are heptane for oily surfaces or isopropyl alcohol for plastics. Do not use household cleaning solvents that contain oils. Carefully read and follow the manufacturer's precautions and directions for use when working with solvents.

Ideal application temperature is from +16°C to +38°C (+60°F to +100°F), bond strength can be improved with firm application pressure and moderate heating from +38°C to +54°C (+100°F to +130°F). Application at temperatures below 10°C (50°F) is not recommended. If application is done at temperatures below 10°C (50°F) surface must be extremely clean, dry and it has to be warmed before attaching the tag to achieve best possible adhesion. Keep the tags in warm before attaching.

Minimum bending diameter of the Confidex Silverline Slim™ is 50mm. Do not bend the label above the limit.

## PRINTER COMPATIBILITY

The Confidex Silverline family is designed and verified to work with the **Custom Zebra ZT410 RFID Silverline** printer. Other Zebra printers are not recommended or supported. Contact your Authorized Zebra Reseller for ordering information.

Set-up instructions and printer configurations specifically for Silverline tags and the Custom ZT410 RFID Silverline printer is available on Zebra.com or by contacting Zebra Technical Support.

## ORDER INFORMATION

**Zebra part number:** 10025344

**Product name:** Confidex Silverline Slim™ M4QT ETSI

**Zebra part number:** 10025341

**Product name:** Confidex Silverline Slim™ M4QT FCC

For additional information and technical support, please contact your Authorized Zebra Reseller or Zebra Technical Support.

## DISCLAIMER

THE MATERIALS, PRODUCTS AND SERVICES ARE SOLD SUBJECT TO ITS STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, CONFIDEX MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN CONFIDEX STANDARD CONDITIONS OF SALE, CONFIDEX AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Confidex products, materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished systems incorporating Confidex products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Confidex.

