

PRODUCT DATASHEET

Confidex Viking™ Sample Kits



Sample kit of 5 Confidex Viking products to get familiar with the capabilities of BLE technology

VIKING FAMILY KEY FEATURES

Device type

Bluetooth® Low Energy beacon, Battery powered

Wireless interface protocol

Bluetooth® 4.2 (ISM 2401 – 2481MHz)

NFC: ISO/IEC 14443A (13,56MHz)

Compliance (Declaration of Conformity)

Europe (CE), USA (FCC), Canada (IC), Japan (MIC), Australia/New Zealand (ACMA), South-Korea (KC), Russia (EAC), Ukraine (UkrSEPRO), Brazil (ANATEL)

Configuration interface

Over NFC interface with Confidex Runestone™ mobile app (available for android mobile phones in Google Play store)

Sensors*

Built-in temperature sensor, accelerometer as option

Read range**

Up to 200 m / 650 ft. Measured on and off metal.

Battery type (total capacity)

2 x CR2477 (2000 mAh) coin battery for maximal lifetime

Expected lifetime***

8 years with typical operating parameters

* Temperature sensor is located inside the plastic housing, which limits real time measurement of the ambient temperature. Sensor calibration is available as additional service.

** Read ranges are measured in laboratory environment and there can be some variation in real application.

*** Beacon lifetime is optimized for long term use, and is highly affected by operating mode parameters, accelerometer usage and ambient temperature. Configured TX power level and advertisement interval have influence on lifetime.

CONFIDEX VIKING™ KEY FEATURES

Reliable industrial grade Bluetooth® Low Energy beacon for industrial identify, sense and locate applications.



Encapsulation

IP68, high quality PC/ASA

Operating temperature

-20°C to +60°C / -4°F to +140°F

Water resistance

Good, tested 5 hours in 1m deep water (IP68)

Vibration resistance

JESD22-B103B, service condition 2;

3-axis vibration with 10G acceleration

Tag dimensions

56 x 55 x 19 mm / 2.20 x 2.13 x 0.75 in (M5 size hole)

CONFIDEX VIKING TOUGH™ KEY FEATURES

Extremely robust industrial grade Bluetooth® Low Energy beacon for industrial applications.



Encapsulation

IP69K, poly-urethan casting

Operating temperature

-40°C to +85°C / -40°F to +185°F

EN 60068-2-14: 2009, Test N: Change of temperature

Water resistance

Submersible (IP69K)

Vibration resistance

EN 60068-2-6: 2008, Test Fc: Vibration, 20G

EN 60068-2-27: 2009, Test Ea: Shock, 40G

Tag dimensions

56 x 54 x 21,3 mm / 2.20 x 2.13 x 0.84 in (M5 size hole)

STANDARD OPERATING MODES



Eddystone



iBeacon



Confidex Viking™ beacon utilizes Eddystone™ open standard frame format and/or iBeacon protocol ensuring straightforward implementation on a wide range of Bluetooth® Low Energy devices.

Confidex Viking™ Classic comes with standard parameters by default. It can be factory configured with customer specific parameters to support any 3rd party system. Confidex™ Viking can also be personalized with a custom label to ease the tag identification in the field.

Following Eddystone™ frame types are supported:

Eddystone™-UID frame broadcasts 16-byte Beacon ID composed of a 10-byte namespace and a 6-byte instance.

Eddystone™-URL frame broadcasts a URL using a compressed encoding format.

Eddystone™-TLM frame broadcasts telemetry information, like battery voltage and temperature.

Eddystone™-EID frame broadcasts an encrypted ephemeral identifier that changes periodically.

Eddystone™-EID frame operating mode requires service for resolving the ephemeral ID. Please contact Confidex for more information.

iBeacon advertise 16 bytes UUID, 2 bytes Major, and 2 bytes Minor.

Accelerometer frame (optional) is a proprietary advertising packet which broadcasts Confidex Viking™ acceleration statistics and activity.

3rd PARTY PLATFORM SUPPORT



Confidex Viking™ sample kits can also be ordered with pre-configured Vikings to Confidex partners ecosystems and platforms such as Quuppa, Here and Wirepas. For more information, please see the product datasheets.

ORDER INFORMATION



Product numbers for standard sample kits:

3002932 Confidex Viking™ Classic Sample Kit

- 5x 3002063 Confidex Viking™ Classic

3003246 Confidex Viking™ Classic Sample Kit

- 5x 3001896 Confidex Viking™ Classic with acc.

3003636 Confidex Viking™ HERE Sample Kit

- 5x 3003242 Confidex Viking™ HERE

3003221 Confidex Viking™ Quuppa Sample Kit

- 5x 3003108 Confidex Viking™ Quuppa

3003637 Confidex Viking™ Wirepas Sample Kit

- 5x 3003404 Confidex Viking™ Wirepas

Availability: Please contact Confidex Smart Industries Sales at www.confidex.com/contact-us

For additional information and technical support, please contact us in contact.BLE@confidex.com

DISCLAIMER

THE MATERIALS, PRODUCTS AND SERVICES ARE SOLD SUBJECT TO ITS STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, CONFIDEX MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN CONFIDEX STANDARD CONDITIONS OF SALE, CONFIDEX AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Confidex products, materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished systems incorporating Confidex products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Confidex.

